## IV71 ICCUE.

# [V7] ISSUE: Cannot perform backup on Linux CLI for backup set created via the AhsayCBS console

Article ID: 5089

Reviewed: 2016-10-14

**Product Version:** 

AhsayCBS / AhsayOBM: 7.3.2.0 to 7.x

OS: Linux

**ATTENTION** 1st January, 2022: v7 officially End-of-Life [details]

## **Problem Description**

For backup set created via the AhsayCBS web console, when attempting to start a backup of any type on Linux CLI (command-line interface), the following error message is received, even when there is no backup job of the same backup set running:

Using APP\_HOME : /usr/local/obm

Using SETTING\_HOME:

...

Running Backup Set - 'backupset name' ...

 $log 4j: WARN\ No\ appenders\ could\ be\ found\ for\ logger\ (org.apache.http.impl.conn. Pooling apache.http.impl.conn. Pooling apache.htm. Pooling apache.$ 

lingClientConnectionManager).

log4j:WARN Please initialize the log4j system properly.

log4j:WARN See http://logging.apache.org/log4j/1.2/faq.html#noconfig for more in fo.

[YYYY/MM/DD hh:mm:ss] start, "Start [ Linux platforms (hostname), AhsayOBM v7.5.0.0 ]",0,0,0,,

[YYYY/MM/DD hh:mm:ss] slpcContent == NULL

[YYYY/MM/DD hh:mm:ss] Another backup job is still running. Backup skipped.

[YYYY/MM/DD hh:mm:ss] end,BS STILL RUNNING,0,0,0,,

#### Note:

This issue will not affect the backup set created via the AhsayOBM user interface on Linux GUI. Also, note that the warning messages "WARN Please initialize the log4j system properly" can be safely ignored. The data integrity check are not affected by the warning (Details).

### Cause

This is a known issue with AhsayOBM 7.3.2.0 - 7.5.0.0, the encryption setting of a backup set is incorrectly configured.

ate: 1/12/15 publici:5089\_issue:cannot\_perform\_backup\_on\_linux\_cli\_for\_backup\_set\_created\_via\_the\_ahsaycbs\_console https://wiki.ahsay.com/doku.php?id=public:5089\_issue:cannot\_perform\_backup\_on\_linux\_cli\_for\_backup\_set\_created\_via\_the\_ahsaycbs\_console

## Resolution

To resolve the issue, for Linux with GUI, login to the AhsayOBM user interface to re-configure the encryption setting of the affected backup set.

For Linux without GUI, patch the AhsayOBM application to version 7.7.0.0 or above. The instructions can be found by Clicking Here.

Execute the RunConfigurator.sh script in the AhsayOBM installation bin directory afterward, to configure the encryption setting for the affected backup set. Refer to the AhsayOBM Linux CLI Quick Start Guide for more details.

# **Keywords**

another, backup, job, running, linux, encrypt, encryption, encrypting

From:

https://wiki.ahsay.com/ - Ahsay Wiki

Permanent link:

https://wiki.ahsay.com/doku.php?id=public:5089\_issue:cannot\_perform\_backup\_on\_linux\_cli\_for\_backup\_set\_created\_via\_the\_ahsaycbs\_console

Last update: 2021/12/15 17:55

https://wiki.ahsay.com/ Printed on 2024/03/29 04:54