

[V8] FAQ: How to start AhsayCBS in debug mode?

Article ID : 8030

Reviewed : 2019-03-19

Product Version:

AhsayCBS: 8.1 to 8.x

OS: All platforms

Description

This article contains instructions on how to start AhsayCBS in debug mode.

Steps

Refer to the following steps to start AhsayCBS in debug mode.

1. Edit the 'cbs.opt' file, located in the installation home and installation home conf folder:

`${Install-Home}\conf`

Value of `${Install-Home}` for various operating system:

- (Windows) C:\Program Files\AhsayCBS
- (Linux/Unix) /usr/local/cbs

2. Open the 'cbs.opt' file with a text editor:

```
cbs.opt (Updated)
...
#
# OBS debug options
# Verify backup data (hashed path, client path, size, block sequence, crc, etc.) during upload
com.ahsay.obs.core.bfs.append.debug=
#
# Verify rebuild operation
com.ahsay.obs.core.bfs.Rebuild.debug=
com.ahsay.obs.core.bfs.debug= true
#
...
```

Note: There are multiple debug options that are available in the 'cbs.opt' file.

Consult with [Ahsay support representatives](#) if you are unsure which debug mode should you enable (e.g. to troubleshoot on your server issue).

3. Save the changes to the 'cbs.opt' file afterward, then restart the AhsayCBS and AhsayCBS NFS service.

Keywords

obs, rebuild, debug, troubleshoot, troubleshooting, cbs

From:

<https://wiki-new.ahsay.com/> - **Ahsay Wiki**

Permanent link:

https://wiki-new.ahsay.com/doku.php?id=public:8030_faq:how_to_start_ahsaycbs_in_debug_mode 

Last update: **2021/12/09 15:36**